# SIMPLY BRILLIANT

Make the right impression and create new stopping power





### Digital Poster Frame

ULTRASLIM & LIGHTWEIGHT INSTALLATION-FRIENDLY It has been engineered with latest technologies to give it a smoother, slimmer profile. It's crafted in beautiful anodized lightweight yet durable aluminum, to make the entire poster frame weigh less than 35kg, making it more portable and easier to install.



Enjoy the privilege of watching or screening your own video, audio or pictures playlists anytime, anywhere. All you've got to do is simply save your content on your USB or SD card and plug into your display. The easy-to-follow on-screen menu makes it absolutely easy to schedule your content and no complicated configuration is needed whatsoever!



You'll love the speedy convenience of doing servicing and panel module replacements from the front with just a handle magnet. Thanks to the patented cableless technology in connecting the modules.



The futuristic Smart Module ingeniously incorporated within each system is its powerhouse. It forms the heart of every display unit and delivers powerful video processing platforms, ensuring all operations converge, thereby ensuring seamless connections like screen monitoring operations and auto-detect work continuously. In addition, the Module's pre-integrated software enables you to connect with a PC or Android devices from a single location via RJ45, WIFI, 3G, USB and HDMI. That makes it so easy to identify your display and manage settings like brightness and contrast or simply play your content directly from your device be it a laptop, tablet or smart phone.



## Deliver the right message at the right time and at the right place

Portable signage solutions that bring innovation and versatility to your business communications



Content can be updated via network or via USB drive and

the content is stored on the unit itself.

-AC Power Adapter Jack

**External Buttons and Connectors** 












#### **ACCESSORIES AND** PACKING





Handle Magnet



\* Non-standard options and accessories. Available as a separate orderable item to complement our LED display solutions

#### CONFIGURATIONS CAN BE CUSTOMIZED







Side Mount



Gustomizable sizes and mounting options available. Sizes are determined by configurations of modules Contact us for more details.

#### **Material Parameters**

Pixel Pitch 2.571 mm Module Size 288 x 216 Display Resolution 112 x 84 LED Configuration SMD 3 in 1 169344 pixels/panel Pixel Density Display Dimension (H x W X D)

1944 x 576 x 35 mm Panel Material Aluminum Frame Colour Black / Silver Weight 35 kg ≥1200cd/m<sup>2</sup> Brightness Drive Mode 1/28 constant scan Viewing Angle 160° (V) / 160° (H) 4.4 Trillion Display Colour Processing Depth 12 bits

Refresh Rate > 1000 Hertz Contrast Ratio 3000:1 Operation Power AC110/240V, 50 - 60Hz

Maximum Power Consumption 600W/panel Average Power Consumption 240W/panel

Display Mode Asynchronous / Synchronous System

Signal Dutput HDMI Connection Type Ethernet / WIFI / 3G

Supported VGA Mode 224 x 756 Supported Video Files MPEG / H.264 -10° to +50° Celsius Operating Temperature

Operating Lifetime (50% Brightness) ≥100,000 Hours Compliance

Features and specifications are subject to change without prior notice

